


- 1) Turn off power.
- 2) Attach mounting strap to outlet box. (Screws not provided).
- 3) Make wire connections (connectors not provided.) Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)




- 4) Raise canopy up, passing canopy over socket. Press canopy against ceiling.
- 5) Keeping canopy flush with ceiling, raise glass up, passing hole in glass over socket.
- 6) Screw socket ring onto socket to hold glass and canopy in place.

- 1) Couper l'alimentation secteur.
- 2) Visser la barrette de montage à la boîte de jonction. (Vis non fournies).
- 3) Effectuer les raccordements électriques (les cosses ne sont pas fournies). Si les fils du lustre ne sont pas noir et blanc, se reporter au tableau ci-dessous pour effectuer les raccordements convenables et câbler en con séquence.

Connecter le fil noir ou rouge de la boîte	Connecter le fil blanc de la boîte
A Noir	A Blanc
*Au cordon parallèle (rond et lisse)	*Au cordon parallèle (à angles droits et strié)
Au transparent, doré, marron, ou noir sans fil distinctif	Au transparent, doré, marron, ou noir avec un fil distinctif
Fil isolé (sauf fil vert) avec conducteur en cuivre	Fil isolé (sauf fil vert) avec conducteur en argent

*Remarque: Avec emploi d'un fil parallèle (SPT I et SPT II). Le fil neutre est à angles droits et strié et l'autre fil doit être rond ou lisse (Voir le schéma).



- 4) Soulever le cache pour le passer par dessus la douille. Appuyer le cache contre le plafond.
- 5) Tout en maintenant le cache à niveau avec le plafond, soulever le verre en passant le trou dans le verre par la douille.
- 6) Visser l'anneau de la douille sur la douille pour fixer le verre et le cache.

INSTRUCTIONS

For Assembling and Installing Fixtures in Canada
Pour L'assemblage et L'installation Au Canada

