




KICHLER PHOTOMETRIC LAB

**Filename:** DTC Slim 4" Square 9W-Photometric Report  
**Manufacturer:** Kichler Lighting LLC  
**Luminaire:** DLSL04S2790WHT  
**Luminaire Cat:** CTR181086-05  
**Lamp:** Integrated LED AC  
**Lamp Output:** Total luminaire Lumens: 573.8  
**Max Candela:** 211.5 at Horizontal: 170°, Vertical: 1°  
**Input Wattage:** 8.7  
**Luminous Opening:** Rectangle (L: 2.52", W: 2.52")  
**Test:** LM-79 Distribution  
**Test Lab:** Kichler Lighting LLC  
**Photometry:** Type C  
**Nema Type:** 7 X 7

**Roadway Summary**

Cutoff Classification:	FULL CUTOFF
Distribution:	Type VS
Max Cd, 90 Deg Vert:	0
Max Cd, 80 to <90 Deg:	23.3
Lumens % Lamp	
Downward Street Side:	286.3 49.9%
Downward House Side:	287.6 50.1%
Downward Total:	573.9 100%
Upward Street Side:	0 0%
Upward House Side:	0 0%
Upward Total:	0 0%
Total Lumens:	573.9 100%

**Flood Summary**



	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	98.4%	564.5	161	160.9
Beam (50%):	70%	401.4	107.7	107.4
Total:	100%	573.7		


**Zonal Lumen Summary**

Zone	Lumens	% Luminaires
0-30	162.6	28.3%
0-40	264.1	46%
0-60	457.6	79.8%
60-90	116.2	20.2%
70-100	48.6	8.5%
90-120	0	0%
0-90	573.8	100%
90-180	0	0%
0-180	573.8	100%

**Lumens Per Zone**

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	20.0	3.5%	90-100	0	0%
10-20	57.1	9.9%	100-110	0	0%
20-30	85.6	14.9%	110-120	0	0%
30-40	101.4	17.7%	120-130	0	0%
40-50	102.9	17.9%	130-140	0	0%
50-60	90.7	15.8%	140-150	0	0%
60-70	67.6	11.8%	150-160	0	0%
70-80	38.9	6.8%	160-170	0	0%
80-90	9.7	1.7%	170-180	0	0%



**Coefficients Of Utilization - Zonal Cavity Method**

RCC %:	80			70			50			30			10			0				
	70	50	30	0	70	50	30	0	50	30	20	0	50	30	20	0	50	30	20	0
RCC: 0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.02	1.00
1	1.09	1.04	1.00	.96	1.06	1.02	.98	.85	.98	.94	.92	.94	.91	.89	.90	.88	.86	.84		
2	.99	.91	.84	.78	.96	.89	.83	.72	.85	.80	.76	.82	.78	.74	.79	.76	.72	.70		
3	.90	.80	.72	.65	.88	.78	.71	.61	.75	.69	.64	.73	.67	.62	.70	.65	.61	.59		
4	.83	.71	.62	.55	.81	.70	.61	.52	.67	.60	.54	.65	.59	.54	.63	.57	.53	.51		
5	.76	.63	.54	.48	.74	.62	.54	.46	.60	.53	.47	.58	.52	.47	.56	.51	.46	.44		
6	.70	.57	.48	.42	.68	.56	.48	.40	.54	.47	.41	.53	.46	.41	.51	.45	.41	.38		
7	.65	.52	.43	.37	.64	.51	.43	.36	.49	.42	.37	.48	.41	.36	.47	.41	.36	.34		
8	.61	.47	.39	.33	.59	.47	.39	.32	.45	.38	.33	.44	.37	.33	.43	.37	.32	.30		
9	.57	.43	.35	.30	.55	.43	.35	.29	.42	.35	.30	.41	.34	.29	.40	.34	.29	.27		
10	.53	.40	.32	.27	.52	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.27	.25		

## Zonal Lumen Tabulation - Flood Type

	-88.75	-86.25	-83.75	-81.25	-78.75	-76.25	-73.75	-71.25	-68.75	-66.25	-63.75	-61.25	-58.75	-56.25	-53.75	-51.25	-48.75	-46.25	-43.75	-41.25	-38.75	-36.25	-33.75	-31.25	-28.75	-26.25	-23.75	-21.25	-19.75
88.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
86.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
83.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
81.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
78.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
76.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
73.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0	
71.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
68.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
66.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
63.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
61.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
58.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
56.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0
53.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0
51.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
48.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
46.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
43.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
41.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
38.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
41.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
43.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
46.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
48.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	
51.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0	

-	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0
-	56.25	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0
-	58.75	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	61.25	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	63.75	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	66.25	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	68.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	71.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
-	73.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0	
-	76.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0	
-	78.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
-	81.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
-	83.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
-	86.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
-	88.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

Maximum Im: 0.4  
Field Im: 564.5  
Total Im: 573.7

### Candela Table - Type C







**Luminaire Report Summary**

[IESNA:LM-63-2002  
[TEST] LM-79 Distribution  
[TESTLAB] Kichler Lighting LLC  
[ISSUEDATE] 6/15/2020  
[MANUFAC] Kichler Lighting LLC  
[LUMCAT] CTR181086-05  
[LUMINAIRE] DLSL0492790WHT  
[LAMP] Integrated LED AC

FILE: CREATED USING ABSOLUTE PHOTOMETRY  
FILE: CANDELA MULTIPLIER: 1  
FILE: VERTICAL ANGLES: 181, HORIZONTAL ANGLES: 73  
FILE: COORDINATE SYSTEM: TYPE C  
FILE: UNIT OF MEASURE: STANDARD  
FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.29 copyright 2003-2020 by jSolutions, Inc.  
Reported data calculated from manufacturer's data file, based on IES recommended methods.