




KICHLER PHOTOMETRIC LAB

Filename: DTC Slim 5" Round 14W-Photometric Report
Manufacturer: Kichler Lighting LLC
Luminaire: DLSL05R2790WHT
Luminaire Cat: CTR181086-03
Lamp: Integrated LED AC
Lamp Output: Total luminaire Lumens: 908.5
Max Candela: 314.9 at Horizontal: 155°, Vertical: 1°
Input Wattage: 13.4
Luminous Opening: Circular (Dia: 4.2")
Test: LM-79 Distribution
Test Lab: Kichler Lighting LLC
Photometry: Type C
Nema Type: 7 X 7






Roadway Summary	
Cutoff Classification:	FULL CUTOFF
Distribution:	Type VS
Max Cd, 90 Deg Vert:	0
Max Cd, 80 to <90 Deg:	39.8
Lumens % Lamp	
Downward Street Side:	453.6 49.9%
Downward House Side:	455.0 50.1%
Downward Total:	908.6 100%
Upward Street Side:	0 0%
Upward House Side:	0 0%
Upward Total:	0 0%
Total Lumens:	908.6 100%

Flood Summary				
	Efficiency	Lumens	Horizontal Spread	Vertical Spread
Field (10%):	98.6%	895.7	163.2	163
Beam (50%):	72.7%	660.2	112.7	112.4
Total:	100%	908.4		

Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	246.1	27.1%
0-40	403.6	44.4%
0-60	712.8	78.5%
60-90	195.8	21.5%
70-100	84.1	9.3%
90-120	0	0%
0-90	908.5	100%
90-180	0	0%
0-180	908.5	100%

Lumens Per Zone		
Zone	Lumens	% Total
0-10	29.8	3.3%
10-20	85.8	9.4%
20-30	130.6	14.4%
30-40	157.5	17.3%
40-50	162.8	17.9%
50-60	146.4	16.1%
60-70	111.7	12.3%
70-80	65.9	7.3%
80-90	18.2	2.0%
Zone	Lumens	% Total
90-100	0	0%
100-110	0	0%
110-120	0	0%
120-130	0	0%
130-140	0	0%
140-150	0	0%
150-160	0	0%
160-170	0	0%
170-180	0	0%



**Coefficients Of Utilization - Zonal Cavity Method**

Effective Floor Cavity Reflectance: 20%

RCC %:	80			70			50			30			10			0		
RW %:	70	50	30	0	70	50	30	0	50	30	20	50	30	20	50	30	20	0
RCR: 0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.00	1.11	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02
1	1.09	1.04	.99	.95	1.06	1.01	.98	.84	.97	.94	.91	.93	.91	.88	.90	.88	.86	.83
2	.99	.90	.83	.78	.96	.88	.82	.71	.85	.79	.75	.82	.77	.73	.78	.75	.71	.69
3	.90	.79	.71	.64	.87	.78	.70	.60	.75	.68	.63	.72	.66	.62	.69	.65	.60	.58
4	.82	.70	.61	.54	.80	.69	.60	.51	.66	.59	.53	.64	.58	.53	.62	.56	.52	.50
5	.76	.63	.54	.47	.73	.61	.53	.45	.59	.52	.46	.57	.51	.46	.55	.50	.45	.43
6	.70	.56	.47	.41	.68	.55	.47	.39	.54	.46	.40	.52	.45	.40	.50	.44	.40	.37
7	.65	.51	.42	.36	.63	.50	.42	.35	.49	.41	.36	.47	.40	.35	.46	.40	.35	.33
8	.60	.47	.38	.32	.59	.46	.38	.31	.45	.37	.32	.43	.37	.32	.42	.36	.31	.29
9	.56	.43	.34	.29	.55	.42	.34	.28	.41	.34	.29	.40	.33	.28	.39	.33	.28	.26
10	.53	.39	.31	.26	.51	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.26	.24

Zonal Lumen Tabulation - Flood Type

-	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.1	
-	56.25	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.3	0.1	
-	58.75	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0	
-	61.25	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0	
-	63.75	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0	
-	66.25	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0
-	68.75	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	71.25	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	73.75	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	76.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0
-	78.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	
-	81.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0
-	83.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-	86.25	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-	88.75	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Maximum Im: 0.6
Field Im: 895.7
Total Im: 908.4

Candela Table - Type C

Luminaire Report Summary

[IESNA] LM-63-2002
[TEST] LM-79 Distribution
[TESTLAB] Kichler Lighting LLC
[ISSUEDATE] 6/15/2020
[MANUFAC] Kichler Lighting LLC
[LUMCAT] CTR181086-03
[LUMINAIRE] DLSL05R2790WHT
[LAMP] Integrated LED AC

FILE: CREATED USING ABSOLUTE PHOTOMETRY
FILE: CANDELA MULTIPLIER: 1
FILE: VERTICAL ANGLES: 181, HORIZONTAL ANGLES: 73
FILE: COORDINATE SYSTEM: TYPE C
FILE: UNIT OF MEASURE: STANDARD
FILE: BALLAST FACTOR: 1

Photometrics Pro 1.3.29 copyright 2003-2020 by jSolutions, Inc.
Reported data calculated from manufacturer's data file, based on IES recommended methods.