© 2022 Kichler Lighting LLC. All Rights Reserved.



### **MOTOR FINISH**



Brushed Nickel

### **BLADE FINISHES**

Champagne



Dimmable

## **AR PERFORMANCE**

**AIRFLOW** Cubic Ft. Per Minute on High

359

**RPM** Revolutions Per Minute on High

318

POWER USAGE Watts on High (Excludes Lights)

32

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

11

#### **SPECIFICATIONS**

Color Rendering Index 80 Kelvin Temperature 3000K Initial Lumens 1600 Diffuser Description Etched Cased Opal Downward-facing Bulbs 1 X 17W Lamp Included Integrated # of Bulbs/LED Modules 1  Photometrics	01 2011 107 11 10110			
Watts (High) 32 Airflow Efficiency CFMW (High) 11  Motor Specifications  Amps (High) 0.25 Motor Size 153MM X 15MM Steel  Mounting/Installation  Minimum Distance from Fan to Floor 78" Location Rating Dry  Max Stem Tilt 22.00  Dimensions  Downrod 1 - Measurement B 19.25" Downrod 1 - Measurement C 10.50" Base Backplate 6.25 DIA Weight 15.87 LBS Blade Sweep 15 Height 15.00"  Light Source  Downlight Included Yes Downlight Included Yes Dimmable Notes Recommended for use with Kickpan Fan Controls  Color Rendering Index 80 Kelvin Temperature 3000K Integrated Downward-facing Bulbs 1 X 17W Lamp Included Integrated Integrated Integrated Integrated Integrated Integrated Downward-facing Bulbs 1 X 17W Lamp Included Integrated Inte	Performance			
Amps (High) Motor Type AC Induction Primary Material Steel  Mounting/Installation  Minimum Distance from Fan to Floor Teet Lead Wire Length 78" Max Stem Tilt Downrod 1 Downrod 1 Downrod 1 - Measurement B Blade Sweep 15 Blade Sweep 15 Bloor Width 15.00"  Light Source Downlight Included Dimmable Yes Downrod 1 Downlight Coption Dimmable Yes Dimmable AB Downlight Option Dimmable Notes Recommended for use with Kicken Temperature Diffuser Description Diffuser Description Lamp Included Hotografed Dimmable Downward-facing Bulbs 1 X 17W Photometrics				
Motor Type AC Induction Primary Material Steel  Mounting/Installation  Minimum Distance from Fan to Floor 78" Location Rating Dry  Max Stem Tilt 22.00  Dimensions  Downrod 1 1.00 OD X 4.50" Downrod 1 - Measurement A 20.00" Downrod 1 - Measurement B 19.25" Downrod 1 - Measurement C 10.50" Base Backplate 6.25 DIA Weight 15.87 LBS Blade Sweep 15 Height 15.00"  Light Source  Downlight Included Yes Downlight Option Dimmable Notes Recommended for use with Kickpan Color Rendering Index Notes 1600 Diffuser Description Etched Cased Opal Downward-facing Bulbs 1 X 17W Lamp Included Integrated  Photometrics	Motor Specifications			
Minimum Distance from Fan to Floor 7 feet Lead Wire Length 78" Location Rating Dry  Dimensions  Downrod 1 1.00 OD X 4.50" Downrod 1 - Measurement A 20.00" Downrod 1 - Measurement B 19.25" Downrod 1 - Measurement C 10.50" Base Backplate 6.25 DIA Weight 15.87 LBS Blade Sweep 15 Height 19.75"  Width 15.00"  Light Source  Downlight Included Yes Downlight Option Dimmable Notes Recommended for use with Kickpan Fan Controls 3000K Initial Lumens 1600 Dimmable Notes Diffuser Description Etched Cased Opal Downward-facing Bulbs 1 X 17W Lamp Included Integrated  Photometrics	. ( 0 )			
Lead Wire Length 78" Location Rating Dry  Max Stem Tilt 22.00  Dimensions  Downrod 1 1.00 OD X 4.50" Downrod 1 - Measurement A 20.00" Downrod 1 - Measurement B 19.25" Downrod 1 - Measurement C 10.50" Base Backplate 6.25 DIA Weight 15.87 LBS Blade Sweep 15 Height 19.75"  Width 15.00"  Light Source  Downlight Included Yes Downlight Option Integrated Recommended for use with Kick Fan Controls  Color Rendering Index 80 Kelvin Temperature 3000K Initial Lumens 1600 Diffuser Description Etched Cased Opal Integrated  Photometrics	Mounting/Installation			
Downrod 1	Lead Wire Length	78"		
Downrod 1 - Measurement B Base Backplate 6.25 DIA Weight 15.87 LBS Blade Sweep 15 Width 15.00"  Light Source  Downlight Included Yes Dimmable Yes Dimmable Ves Dimmable Ves Dimmable Ves Dimmable Color Rendering Index Base Backplate Base Base Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base Base LBS Base Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base Base LBS Base Base Base Base LBS Base Base Base Base LBS Base Base Base LBS Base Base Base Base LBS Base Base Base Base LBS Base Base LBS Base Base Base LBS Base Base LBS Base Base Base LBS Ba	Dimensions			
Downlight Included Pimmable Pes Dimmable Yes Dimmable Yes Dimmable Notes Pecommended for use with Kick Fan Controls Color Rendering Index Initial Lumens Integrated Recommended for use with Kick Fan Controls South Fan Controls Fan	Downrod 1 - Measurement B Base Backplate Blade Sweep	19.25" 6.25 DIA 15	Downrod 1 - Measurement C Weight	10.50" 15.87 LBS
Dimmable Yes Dimmable Notes Recommended for use with Kick Fan Controls  Color Rendering Index 80 Kelvin Temperature 3000K  Initial Lumens 1600 Diffuser Description Etched Cased Opal  Downward-facing Bulbs 1 X 17W Lamp Included Integrated  # of Bulbs/LED Modules 1  Photometrics	Light Source			
Initial Lumens 1600 Diffuser Description Etched Cased Opal Downward-facing Bulbs 1 X 17W Lamp Included Integrated # of Bulbs/LED Modules 1  Photometrics	•		• .	Recommended for use with Kichler
	Initial Lumens Downward-facing Bulbs	1600	Diffuser Description	Etched Cased Opal
Color Temperature Range 3000 Delivered Efficacy (Lumens/Watt) 94	Photometrics			
20.000 (10.000) (10.000)	Color Temperature Range	3000	Delivered Efficacy (Lumens/Watt)	94

#### **FIXTURE ATTRIBUTES**

Blade Finish & Specs			
Blade Finish 1 Blades Included	Champagne Yes	Blade Material Number of Blades	Polycarbonate 5
Included Control			
Remote Included	Yes		
Product/Ordering Information			
SKU UPC	300230Nl 783927450904	Finish Style	Brushed Nickel Contemporary
Warranty			

# **ALSO IN THIS FAMILY**

www.kichler.com/warranty





300230OBB

300230WH

You can see all products in this family by searching  ${\bf Kichler.com}$