


MOTOR FINISH



BLADE FINISHES

Bsh Stain Steel



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
8666	267	91	95

SPECIFICATIONS

Performance			
CFM (High)	8666	RPM (High)	267
Watts (High)	91	Airflow Efficiency CFM/W (High)	95
Motor Specifications			
Amps (High)	0.79	Motor Size	188MM X 20MM
Motor Type	AC Induction	Primary Material	Steel
Mounting/Installation			
Minimum Distance from Fan to Floor	10 feet	Interior/Exterior	Interior
Lead Wire Length	78"	Location Rating	CSA UL Listed Dry
Low Ceiling Adaptable	No	Max Stem Tilt	30.00
Dimensions			
Downrod 1	1.00 OD X 8.00"	Downrod 1 - Measurement A	15.00"
Downrod 1 - Measurement B	12.25"	Downrod 1 - Measurement C	7.50"
Base Backplate	5.25" DIA	Weight	18.30 LBS
Blade Sweep	56	Height	15.00"
Width	56.00"		
FIXTURE ATTRIBUTES			
Blade Finish & Specs			
Blade Finish 1	Bsh Stain Steel	Blade Material	Steel
Blade Pitch	7	Blades Included	Yes
Number of Blades	3		
Included Control			
Wall Control Included	Yes	Remote Included	No
Control Type	337012.00		

Product/Ordering Information

SKU	330025BSS	Finish	Brushed Stainless Steel
UPC	783927521277	Style	Transitional

Housing

Fan Primary Control System	4 Spd Wall Slide Control
----------------------------	--------------------------

Warranty

www.kichler.com/warranty

Compatible Accessories

4 Speed Wall Control Rotary 10 Amp Brushed Aluminum, 4 Speed Fan Slide Control White, 4 Speed Wall Control Rotary 5 Amp Multiple Finishes

ALSO IN THIS FAMILY



330025SBK



330025WH

You can see all products in this family by searching **Kichler.com**