



MOTOR FINISH

● Brushed Stainless Steel

BLADE FINISHES

Silver

Ⓛ LED Light Kit

AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
1226	1100	44	28

CFM (Low)	603
RPM (Low)	548
Watts (Low)	22

SPECIFICATIONS

Light Source			
Downlight Option	Removable	Watts (High)	44
Watts (Low)	22	Lamp Included	Included
Lamp Type	ST19	Light Source	LED
# of Bulbs/LED Modules	3	Optional Light Kit Available	Removable
Socket Type	Medium		
Photometrics			
Color Rendering Index	90	Delivered Efficacy (Lumens/Watt)	114
Kelvin Temperature	2700K		
Electrical			
Amps (High)	0.41	Amps (Low)	0.32
Motor Size	8225X1	Motor Type	AC
Supply Wire (Degrees)	90		
Dimensions			
Downrod 1	1.00" OD X 6.00"	Base Backplate	5.75 DIA
Weight	28.60 LBS	Height	17.75"
Width	23.00"		
Mounting/Installation			
Minimum Distance from Fan to Floor	7.0 feet	Interior/Exterior	Interior
Lead Wire Length	78"	Location Rating	Dry
Mounting Style	Downrod	Mounting Weight	27.00 LBS

FIXTURE ATTRIBUTES

Product/Ordering Information			
SKU	300041BSS	Finish	Brushed Stainless Steel
Style	Industrial	UPC	783927603980

Housing

Fan Primary Control System	3 Speed Wall Control Limited Function	Wall Control Included	Yes
Primary Material	STEEL	Max Stem Tilt	30.00

Blade Finish & Specs

Blade Finish 1	SILVER	Blade Material	ABS
Blade Pitch	21	Blade Sweep	13
Blades Included	Yes	Number of Blades	3

Warranty

www.kichler.com/warranty

ALSO IN THIS FAMILY



300041SBK

You can see all products in this family by searching **Kichler.com**